



## CABLE SPECIFICATION

**Part:** 04S18A2

**Desc:** 18/2 Sol Shielded Fire Wire PVC FPLR



<b>AWG</b>	18 Awg Solid Bare Copper
<b>CONDUCTORS:</b>	2
<b>INSULATION:</b>	Polyethylene
<b>Nominal Wall</b>	.006"
<b>Shield</b>	Aluminum Mylar
<b>Color Code</b>	Black, Red
<b>% Overlap</b>	20
<b>Drain</b>	24 Awg Stranded Tinned Copper
<b>Jacket</b>	PVC - Red
<b>Nominal Wall</b>	.014"
<b>Nominal OD</b>	.146"
<b>Nom Capacitance pF/Ft</b>	39 Cond/Cond    72 Cond/Drain
<b>TEMPERATURE RATING</b>	75C
<b>OPERATING VOLTAGE</b>	300V
<b>CHARACTERISTICS</b>	Twisted with an aluminum mylar shield & jacketed
<b>PRINT</b>	(3090194) 18 Awg CMR or CL2R or FPLR 75C (ETL) US 2 COND SHD Made in USA

AllStar Cable Products, Inc. makes no warranties as to the suitability of a product chosen for a particular use.  
 Specifications subject to change without notice.

Spec issue date: 1-19-17

**9837 Pioneer Blvd., Santa Fe Springs, CA 90670 Phone: (562)463-9160 Fax: (562)463-9170**