



## CABLE SPECIFICATION

**Part:** 3222B2

**Desc:** 22/2 Stranded Non-Shielded H20 Cable CM/CL2/FPL  
Direct Burial (In Conduit) "Sun Res" Waterblock Tape



<b>AWG</b>	22 Awg 7 Strand Bare Copper
<b>CONDUCTORS:</b>	2
<b>INSULATION:</b>	PVC
<b>Nominal Wall</b>	0.01
<b>Shield</b>	Waterblocking Tape
<b>Color Code</b>	Blk, Red
<b>% Overlap</b>	20
<b>Drain</b>	NA
<b>Jacket</b>	PVC / Black
<b>Nominal Wall</b>	.025"
<b>Nominal OD</b>	.170"
<b>TEMPERATURE RATING</b>	60C
<b>OPERATING VOLTAGE</b>	300V
<b>CHARACTERISTICS</b>	Twisted together with a waterblocking tape and jacketed
<b>PRINT</b>	22 Awg CM or CL2 or FPL 75C C(ETL) US 2 COND "Direct Burial In Conduit" Sun-Res Made In USA

AllStar Cable Products, Inc. makes no warranties as to the suitability of a product chosen for a particular use.  
Specifications subject to change without notice.

Spec issue date: 1-19-17

**9837 Pioneer Blvd., Santa Fe Springs, CA 90670 Phone: (562)463-9160 Fax: (562)463-9170**