



## CABLE SPECIFICATION

**Part:** 32S14B2

**Desc:** 14/2 Stranded Shielded H20 Cable CM/CL2/FPL  
Direct Burial (In Cinduit) Waterblock Tape



<b>AWG</b>	14 Awg 7 Strand Bare Copper
<b>CONDUCTORS:</b>	2
<b>INSULATION:</b>	PVC
<b>Nominal Wall</b>	.010"
<b>Shield</b>	Waterblocking Shield Tape
<b>Color Code</b>	Blk, Red
<b>% Overlap</b>	20
<b>Drain</b>	16 Awg 26 Strand Tinned Copper
<b>Jacket</b>	PVC / Black
<b>Nominal Wall</b>	.025"
<b>Nominal OD</b>	.259"
<b>TEMPERATURE RATING</b>	75C
<b>OPERATING VOLTAGE</b>	300V
<b>CHARACTERISTICS</b>	Twisted together with a Waterblocking Shld Tape and Jacketed
<b>PRINT</b>	14 Awg CM or CL2 or FPL 75C (ETL) US Shld 2 COND "Direct Burial In Cinduit"      Made in USA

AllStar Cable Products, Inc. makes no warranties as to the suitability of a product chosen for a particular use.  
 Specifications subject to change without notice.

Spec issue date: 1-19-17

**9837 Pioneer Blvd., Santa Fe Springs, CA 90670 Phone: (562)463-9160 Fax: (562)463-9170**