



## CABLE SPECIFICATION

**Part:** P03IS18B2

**Desc:** 18/2 Pair Stranded Individually Shielded Plenum CMP



<b>AWG</b>	18 Awg 7 Strand Bare Copper
<b>CONDUCTORS:</b>	4 (2 Pairs)
<b>INSULATION:</b>	PVC-Plenum
<b>Nominal Wall</b>	.008"
<b>Shield</b>	Aluminum Mylar
<b>Color Code</b>	Blk, Red - Blk, Wht
<b>% Overlap</b>	20
<b>Drain</b>	20 Awg 7 Strand Tinned Copper (Common Drain)
<b>Jacket</b>	Plenum / White
<b>Nominal Wall</b>	.015"
<b>Nominal OD</b>	.253"
<b>TEMPERATURE RATING</b>	75C
<b>OPERATING VOLTAGE</b>	300V
<b>CHARACTERISTICS</b>	Twisted, Shielded and Jacketed
<b>PRINT</b>	18 Awg CMP or CL2P or FPLP 75C (ETL) US SHLD 4 COND Made in USA

AllStar Cable Products, Inc. makes no warranties as to the suitability of a product chosen for a particular use.  
 Specifications subject to change without notice.

Spec issue date: 1-19-17

**9837 Pioneer Blvd., Santa Fe Springs, CA 90670 Phone: (562)463-9160 Fax: (562)463-9170**